

2100IF

THREE NEEDLE COVERSTITCH SEWING MACHINE WITH DIRECT DRIVE



The 2100IF flatbed coverstitch machine with advanced Direct Drive technology provides the flexibility of using either 2 or 3 needles for hemming, cover seaming as well as collarete work (with optional attachments). Direct Drive means there's no more belt to replace and you get the most accurate speed control to fit every level of sewer's needs.

With easy to thread looper, no stain seal to trap and prevent oil from leaking, built-in release mechanism to allow for easy removal of the material and an eye and needle guard for your safety.

SPECIFICATIONS

ELECTRICAL	110V/120V / 60hz	
MAXIMUM SEWING SPEED	6,000 RPM	
MAX STITCH LENGTH	0.17"	4.4 mm
PRESSER FOOT LIFT	0.25" (with limiter)	6.3 mm (with limiter)
NEEDLE SYSTEM #	UY128GAS	
NEEDLE GAUGE	0.22" or 0.25"	5.6 or 6.4 mm
NEEDLE BAR STROKE	1.22"	31 mm
LUBRICATION	Automatic	
DIRECT DRIVE TECHNOLOGY	Yes	
COUNTRY OF ORIGIN	China	
WARRANTY	Limited 1 Year	

COVER-SEAMING MADE EASY



DIFFERENTIAL FEED



STITCH REGULATOR



UBERLIGHT INCLUDED



SUPERIOR STAND



2 OR 3 NEEDLE OPERATION



DIRECT DRIVE



NO STAIN SEAL