

3200TN

TWO NEEDLE LOCKSTITCH, NEEDLE FEED



When sewing multiple plies of fabric together or for top stitching, if the fabric is slippery, or if puckering is an issue, the 3200TN is the right machine for the job. It is suitable for sewing from light to medium weight fabric.

For sewing flags, banners, and synthetics, the 3200TN with safety clutch, drop in bobbins and automatic oiling offers the whole package. Low noise and vibration design, outstanding build quality and reliability and the industries #1 DC servomotor.

SPECIFICATIONS

ELECTRICAL	110V/120V / 60hz	
MAXIMUM SEWING SPEED	4,000 RPM	
NEEDLE GAUGE	1/4" standard	6.4 mm standard
STITCH LENGTH	0 - 0.2"	0 - 5 mm
NEEDLE BAR STROKE	1.31"	33.4 mm
PRESSURE FOOT LIFT	By hand 0.28" By knee 0.51"	By hand 7 mm By knee 13 mm
NEEDLE SYSTEM #	135 x 5	
FEED DOG	2 rows each	
HOOK TYPE	Rotary - auto lubricated	
LUBRICATION	Automatic	
STITCH DIAL REGULATOR	Yes	
REVERSE LEVER	Yes	
COUNTRY OF ORIGIN	China	
WARRANTY	Limited 1 year	

QUALITY
YOU CAN
COUNT ON



**STITCH DIAL &
REVERSE LEVER**



1/4" GAUGE STANDARD



SEWQUIET SERVOMOTOR



SUPERIOR STAND



**UBERLIGHT™ FLEX
3100TL INCLUDED**

3200TN

TWO NEEDLE LOCKSTITCH, NEEDLE FEED

