

SINGLE NEEDLE LOCKSTITCH, WALKING FOOT

SPECIFICATIONS

ELECTRICAL	110V/120V / 60hz	
MAXIMUM SEWING SPEED	2,000 RPM	
STITCH LENGTH	0 - 0.35"	0 - 9 mm
NEEDLE BAR STROKE	1.42''	36 mm
PRESSURE FOOT LIFT	By hand 0.35" By knee 0.75"	By hand 9 mm By knee 19 mm
AUTO FOOT LIFT	9/16	
NEEDLE SYSTEM #	135 x 17	
SAFETY CLUTCH	Yes	
FEED DOG	Single row	
HOOK TYPE	Rotary - auto lubricated	
LUBRICATION	Semi-automatic	
STITCH DIAL REGULATOR	Yes	
REVERSE LEVER	Yes	
COUNTRY OF ORIGIN	China	
WARRANTY	Limited 1 year	

The new third-generation 4220SW improves on our best-selling walking foot, compound feed sewing machine with the inclusion of Direct Drive Technology. Equipped with a convenient height adjustment lever to accommodate different thicknesses of material. Whether you're sewing upholstery, bags, heavy canvas, or a variety of other heavy materials, the 4220SW is built tough.

Direct Drive offers the best user experience. From index stitching to a programmable needle positioner to digital speed control, the 4220SW is the Walking Foot Sewing machine you have been waiting for. Ideal for sewing medium to heavyweight leather, upholstery, canvas, and synthetics.





4220SW

SINGLE NEEDLE LOCKSTITCH, WALKING FOOT



