

5600SO

THREE-FIVE THREAD HIGH-SPEED SAFETY SERGER



For joining two or more plies of fabric together (3 or 5 threads), or for "overedging" (3 threads), the 5600SO is a machine with a lot of versatility. It produces a soft seam, even at high speeds, and is suitable for light to medium weight fabrics.

For sewing all kinds of woven and knit fabrics, the 5600SO with differential feed, stitch length regulator and fully automatic lubrication offers the whole package. Low noise and vibration design, outstanding build quality and reliability.

SPECIFICATIONS

ELECTRICAL	110V/120V / 60hz	
MAXIMUM SEWING SPEED	6,000 RPM	
PRESSER FOOT LIFT	0.22"	5.5 mm
MAX STITCH LENGTH	0.15"	3.8 mm
NEEDLE GAUGE	0.12"	3 mm
OVEREDGING WIDTH	0.20"	5 mm
OVERALL SEAM BITE	0.31"	8 mm
DIFFERENTIAL RATIO	1:08 - 1:19	
NEEDLE BAR STROKE	0.93"	23.7 mm
NEEDLE SYSTEM #	B27	
LUBRICATION	Automatic	
COUNTRY OF ORIGIN	China	
WARRANTY	Limited 1 year	


QUALITY
YOU CAN
COUNT ON



TENSION DIALS



AUTOMATIC LUBRICATION



DIFFERENTIAL FEEDING



CONTROL PANEL



DIRECT DRIVE MOTOR



UBERLIGHT™ FLEX
3100TL INCLUDED



COMPLETE STAND

5600SO

THREE-FIVE THREAD HIGH-SPEED SAFETY SERGER

